



CLEARANCE TO COMBUSTIBLES CORR/GUARD

CORR/GUARD SINGLE WALL (CGSW, FCSSW & FCGSW)

RATED OPERATING TEMPERATURE		MINIMUM CLEARANCE ENCLOSED		MINIMUM CLEARANCE UNENCLOSED	
DIAMETER	TEMPERATURE	HORIZONTAL	VERTICAL	HORIZONTAL	VERTICAL
CGSW-Single Wall 3" & 4" (76mm -102mm)	400°F(204°C)	8"(203)	4"(102)	1"(25)	1"(25)
	480°F(249°C)	8"(203)	4"(102)	2"(51)	2"(51)
	550°F(288°C)	N/A	N/A	2"(51)	2"(51)
CGSW-Single Wall 5" (127mm)	400°F(204°C)	N/A	6"(152)	1"(25)	1"(25)
	480°F(249°C)	N/A	6"(152)	2"(51)	2"(51)
	550°F(288°C)	N/A	N/A	2"(51)	2"(51)
FCSSW-Single Wall 6"-12"(152mm-305mm)	480°F(249°C)	N/A	N/A	2"(51)	2"(51)
	550°F(288°C)	N/A	N/A	2"(51)	2"(51)
FCSSW-Single Wall 14"-18"(356mm-457mm)	480°F(249°C)	N/A	N/A	3"(76)	3"(76)
	550°F(288°C)	N/A	N/A	3"(76)	3"(76)
FCSSW-Single Wall 20"-24"(508mm-610mm)	480°F(249°C)	N/A	N/A	4"(102)	4"(102)
	550°F(288°C)	N/A	N/A	4"(102)	4"(102)
FCGSW-Single Wall 26"-30"(660mm-762mm)	480°F(249°C)	N/A	N/A	5"(127)	5"(127)
	550°F(288°C)	N/A	N/A	5"(127)	5"(127)
FCGSW-Single Wall 32"-36"(813mm-914mm)	480°F(249°C)	N/A	N/A	6"(152)	6"(152)
	550°F(288°C)	N/A	N/A	6"(152)	6"(152)

CORR/GUARD DOUBLE WALL (CG, FCS, FCS-1, FCG, & FCG-1)

RATED OPERATING TEMPERATURE		MINIMUM CLEARANCE ENCLOSED		MINIMUM CLEARANCE UNENCLOSED	
DIAMETER	TEMPERATURE	HORIZONTAL	VERTICAL	HORIZONTAL	VERTICAL
CG-Double Wall 3" - 5" (76mm -127mm)	300°F(149°C)	3"(76)	1"(25)	1"(25)	1"(25)
	480°F(249°C)	6"(152)	1"(25)	1"(25)	1"(25)
	550°F(288°C)	N/A	1"(25)	1"(25)	1"(25)
FCS/FCS-1-Double Wall 6"-12"(152mm-305mm)	480°F(249°C)	N/A	1"(25)	1"(25)	1"(25)
	550°F(288°C)	N/A	1"(25)	1"(25)	1"(25)
FCS/FCS-1-Double Wall 14"-18"(356mm-457mm)	480°F(249°C)	N/A	1"(25)	2"(51)	1"(25)
	550°F(288°C)	N/A	1"(25)	2"(51)	1"(51)
FCS/FCS-1-Double Wall 20"-24"(508mm-610mm)	480°F(249°C)	N/A	1"(25)	3"(76)	1"(25)
	550°F(288°C)	N/A	1"(25)	3"(76)	1"(25)
FCG/FCG-1-Double Wall 26"-30"(660mm-762mm)	480°F(249°C)	N/A	2"(51)	4"(102)	2"(51)
	550°F(288°C)	N/A	2"(51)	4"(102)	2"(51)
FCG/FCG-1-Double Wall 32"-36"(813mm-914mm)	480°F(249°C)	N/A	2"(51)	5"(127)	2"(51)
	550°F(288°C)	N/A	2"(51)	5"(127)	2"(51)